

# CSS-8006BM Full-Range Loudspeaker for Paging and Background Music Applications

#### **Commercial Series**

#### **Key Features:**

- ► Affordably priced, high-quality dual-cone ceiling
- ▶ Pre-assembled speaker / transformer grille assembly
- ► Suitable for most paging or background music applications, including retail stores, restaurants, schools and other facilities
- ▶ Very high sensitivity providing maximum sound levels using minimal amplifier power
- ▶ Multi-tap transformer for 100V and 70V distributed speaker lines
- Easy blind-mount installation from below the ceiling with spring clamp
- Deptional CSS-BB6BM backcan for inhibiting fire, preventing dust, and limiting sound from the back of the speaker

JBL Commercial® CSS-8006BM ceiling speaker provides excellent performance for paging and background music applications. High sensitivity provides maximum sound level, even at low tap settings.

The CSS-8006BM speaker is a 165 mm (6.5") speaker with high 94 dB sensitivity, great bass extension in open-back configuration, and a 6W (100V) multi-tap transformer.

The speaker's pre-attached dual-voltage transformer provides versatility by allowing use on 100V or 70V distributed loudspeaker lines.

The drivers features a full 14 mm (0.55") diameter voice coil with a better power dissipation and long-term reliability. For installation convenience, the speaker grille and transformer are pre-attached to the driver. Grilles are powder-coated steel. Matching CSS-BB6BM backcan is made of dark gray powder-coated steel. The backcan can be installed to the speaker and wired prior to installation of the speaker.



#### **Specifications:**

System:		
	Frequency Range (-10 dB) <sup>1</sup> :	70 Hz-20 kHz
	Power Capacity <sup>2</sup> :	6 W (100 hrs)
	Sensitivity <sup>1</sup> :	94 dB (1 W[2.83 V]), 1 m, 300 Hz~16 KHz, driver)
	Coverage (2 kHz) <sup>3</sup> :	120°
	Nominal Driver Impedance:	8 ohms
	Transformer Insertion Loss:	1.5 dB Maximum
	Transformer Taps:	100V: 6W, 3W, 1.5W
		70V: 3W, 1.5W, 0.8W
Physical:		
•	Cutout Size:	175 mm (6.89 in)
	Outside Dimensions (H x Dia):	66 mm x 200 mm (2.6 in x 7.87 in)
	Net Weight (each):	0.63 kg( 1.4 lb)
	Shipping Weight (each):	0.85 kg (1.88 lb)
	Optional Accessories:	CSS-BB6BM backcan

<sup>&</sup>lt;sup>1</sup> Half-space (flush mounted in ceiling)

<sup>&</sup>lt;sup>2</sup> IEC standard, full bandwidth pink noise with a 6 dB crest factor for specified period.


<sup>&</sup>lt;sup>3</sup> -6 dB from the axis

### CSS-8006BM Full-Range Loudspeaker for Paging and Background Music Applications


#### Frequency Response:

## Half-space (flush mounted in the ceiling) SPL, 1W//1m (dB) 10000

#### **Installation:**




### Coverage:





Frequency (Hz)


Installing with Backcan





#### **Dimensions:**











8500 Balboa Boulevard, P.O. Box 2200 Northridge, California 91329 U.S.A.

© Copyright 2011 JBL Professional www.jblpro.com

JBL Professional

